## **Amendments to the Claims**

## This listing of claims will replace all prior versions and listings of the claims:

- 1. (currently amended) A method of validating an e-ticket, comprising the steps of:
- a) sending the e-ticket from an initial receiving server  $S_i$  to a plurality of servers including  $S_i$ , wherein each server returns an answer indicative of whether that server previously answered an inquiry for the e-ticket;
  - b) collecting the identities of the answering servers in an answer set;
- c) broadcasting the e-ticket and the answer set to the plurality of servers, if at least one server previously answered an inquiry for the e-ticket; and
- d) collecting the identity of any server  $S_k$  broadcasting the e-ticket and an associated answer set in a second answer set upon receipt of the broadcast; and
- e) rejecting the e-ticket if the answer set is a subset of the second answer set, wherein steps a), b), c), and d), and e) are performed to validate the e-ticket and wherein step d) is repeated as long as S<sub>i</sub> has not received its own broadcast and there is no server S<sub>k</sub> in the second answer set such that the associated answer set is a subset of the second answer set.
- 2. (original) The method of claim 1 wherein step b) is performed until a majority of servers has answered.
- 3. (canceled)
- 4. (previously presented) The method of claim 1 further comprising the step of:
- e) accepting the e-ticket if  $S_i$  receives its own broadcast and the answer set is a subset of the second answer set.
- 5. (currently amended) The method of claim 1 further comprising the step of:
- d)-rejecting the e-ticket if S<sub>i</sub> has received its own broadcast and the answer set is not a subset of the second answer set.

Application No.: 09/839,664 Response to Final OA of 09/22/06

- 6. (currently amended) A method of validating an e-ticket, comprising the steps of:
- a) sending the e-ticket from an initial receiving server  $S_i$  to a plurality of servers including  $S_i$ , wherein each server returns an answer indicative of whether that server previously answered an inquiry for the e-ticket;
  - b) collecting the identities of the answering servers in an answer set;
- c) broadcasting the e-ticket and the answer set to the plurality of servers, if-at least one server previously answered an inquiry for the e-ticket;
- d) collecting the identity of any server  $S_k$  broadcasting the e-ticket and an associated answer set in a second answer set, upon receipt of the broadcast; and
- e) rejecting the e-ticket if the answer set is a subset of the second answer set, wherein steps a) through e) are performed to validate the e-ticket and S<sub>i</sub> has not received its own broadcast.
- 7. (original) The method of claim 1 wherein the e-ticket represents a prior reservation of goods or services.
- 8. (original) The method of claim 1 wherein the e-ticket contains no information specifically identifying the owner.
- 9. (original) The method of claim 1 wherein broadcasts are performed in accordance with a selected one of a pure atomic broadcast, a general broadcast, a CT-broadcast, and an OPT-broadcast protocol.
- 10. (currently amended) A method of validating an e-ticket, comprising the steps of:
- a) sending the e-ticket from an initial receiving server  $S_i$  to a plurality of servers including  $S_i$ , wherein each server returns an answer indicative of whether that server previously answered any inquiry for the e-ticket;
- b) selecting a conflict mode if at least one selected server of a majority of servers answered a previous inquiry for the e-ticket; and

Application No.: 09/839,664 Response to Final OA of 09/22/06

- c) selecting a conflict-free mode if none of the majority of servers has answered any previous inquiry for the e-ticket, wherein steps a), b), and c) are performed to validate the e-ticket and wherein step b) further comprises the steps of:
  - i) broadcasting the e-ticket and the answer set to the plurality of servers; and
- ii) collecting the identity of any server  $S_k$  broadcasting the e-ticket and an associated answer set in a second answer set; and
- $\underbrace{\text{iii) rejecting the e-ticket if the answer set is a subset of the second answer set}_{\text{the broadcast; and wherein step b) (ii) is repeated as long as <math>S_i$  has not received its own broadcast and there is no server  $S_k$  in the second answer set such that the associated answer set  $\subseteq$  the second answer set in order to validate the e-ticket.
- 11. (original) The method of claim 10 wherein step c) further comprises the step of:
  i) accepting the e-ticket.
- 12. (previously presented) The method of claim 10 further comprising the step of:
  - d) collecting the identities of the answering servers in an answer set.
- 13. (canceled)
- 14. (canceled)
- 15. (previously presented) The method of claim 10 further comprising the step of accepting the e-ticket if  $S_i$  receives its own broadcast and the answer set  $\subseteq$  the second answer set.
- 16. (previously presented) The method of claim 10 further comprising the step of rejecting the e-ticket if  $S_i$  has received its own broadcast and the answer set is not a subset of the second answer set.
- 17. (previously presented) The method of claim 10 further comprising the step of:

Application No.: 09/839,664 Response to Final OA of 09/22/06

d) rejecting the e-ticket if the answer set  $\subseteq$  the second answer set and  $S_i$  has not received its own broadcast.

18. (original) The method of claim 10 wherein the e-ticket represents a prior reservation of goods or services.

19. (original) The method of claim 13 wherein broadcasts are performed in accordance with a selected one of a pure atomic broadcast, a general broadcast, a CT-broadcast, and an OPT-broadcast protocol.